

DRE Transport 5000 Plus

Anesthesia Machine

Equipment for the way *you* operate



Portable anesthesia system designed for office-based surgery centers and small facilities in which space is at a premium.

Compact for mobility and cost-effective to save you money, the Transport 5000 Plus has integrated safety functions and is easy to use and maintain.

Specifications:

Gas supply

- Pipeline gas: O₂
- Output pressure of regulator: 280kPa-300kPa
- Security valve discharge pressure: ≤ 600 kPa
- Pressure of pipeline inlet: 280kPa-600kPa

Flowmeter

- Gas: scale
- O₂: 0.0L/min ~10L/min
- Precision: At 20, atmospheric pressure is 101.3kPa, the precision of flowmeter is level: 2.5.
- O₂ flushing: 35L/min ~ 75L/min

Respiration System

- Absorbent: 1000mL
- System leakage: When pressure is lower than 3kPa, ≤ 125 mL/min
- System compliance: ≤ 4 mL/kPa
- Resistance of ventilator system:
- Flow-rate: 30L/min < 0.16 kPa
- Flow-rate: 60L/min < 0.52 kPa
- APL valve $\sim 0.19-6$ kPa

Dimensions

- Height 20.47 in. (520mm)
- Width 19.29 in. (490mm)
- Depth 11.41 in (290mm)
- Weight 45 lbs (20kg)

