

# DRE Comfort Series

## Available in 9 different styles

All come standard with rapid warm time and digital controls.

- » Heights between 24.5" and 74.5".
- » Doors with full-view glass or opaque stainless steel.
- » Up to three adjustable shelves.
- » Temperature range of 90° - 160° F.
- » Digital controls, dual display, rapid warm time and uniform heating.
- » Choose a stainless or full view glass door.



**Comfort Compact**



**Comfort Dual View**

### A Quick Look

- » Easy to use.
- » Digitally-controlled heating chambers.
- » Rapid warm time (two to six hours, depending on load).
- » Uniform heating.
- » Heating range of 90° to 160° F.
- » Fully insulated.
- » UL/CUL-approved.
- » Audible and visual over-temp alarm.
- » Available with optional keyed temperature lockout and door lock.



# DRE Comfort Series

Blanket and Fluid Warmers

Equipment for the way *you* operate

## Choose your configuration



**Comfort Dual**  
**Overall Size (h x w x d)**  
74.5" x 30" x 26.5"  
17.2 cubic-ft. storage  
**Upper Chamber I.D.**  
15.25" x 26" x 23"  
5.27 cubic-ft. storage  
**Lower Chamber I.D.**  
34.5" x 26" x 23"  
11.93 cubic-ft. storage  
**Electrical**  
120 V, 15 Amp.,  
50/60 Hz, .75 kw/hr,  
2,557 btu/hr, UL/CUL

**Features:** Push button independent controls, three adjustable shelves, accuracy upper:  $\pm 1^\circ$  F, lower:  $\pm 3^\circ$  F (shown here on optional dolly)



**Comfort VC21**  
**Overall Size (h x w x d)**  
74.5" x 30" x 26.5"  
**Chamber I.D.**  
61" x 26" x 23"  
21 cubic-ft. storage  
**Electrical**  
120 V, 7.5 Amp.,  
50/60 Hz, .53 kw/hr,  
1,810 btu/hr, UL/CUL

**Features:** Push button operation, two adjustable shelves, two fixed shelves, accuracy  $\pm 3^\circ$  F (shown here on optional dolly)

**Comfort Dual View**  
**Overall Size (h x w x d)**  
74.5" x 30" x 26.5"  
17.2 cubic-ft. storage  
**Upper Chamber I.D.**  
15.25" x 26" x 23"  
5.27 cubic-ft. storage  
**Lower Chamber I.D.**  
34.5" x 26" x 23"  
11.93 cubic-ft. storage  
**Electrical**  
120 V, 15 Amp.,  
50/60 Hz, .75 kw/hr,  
2,557 btu/hr, UL/CUL

**Features:** Push button independent operation, three adjustable shelves, accuracy upper:  $\pm 1^\circ$  F, lower:  $\pm 3^\circ$  F



**Comfort VC9**  
**Overall Size (h x w x d)**  
36" x 30" x 26.5"  
**Chamber I.D.**  
25" x 26" x 23"  
8.63 cubic-ft. storage  
**Electrical**  
120 V, 7.5 Amp.,  
50/60 Hz, .35 kw/hr,  
1,195 btu/hr, UL/CUL

**Features:** Push button operation, two adjustable shelves, accuracy  $\pm 2^\circ$  F



**Comfort VC5**  
**Overall Size (h x w x d)**  
24.5" x 30" x 26.5"  
**Chamber I.D.**  
15.25" x 26" x 23"  
5.27 cubic-ft. storage  
**Electrical**  
120 V, 7.5 Amp.,  
50/60 Hz, .30 kw/hr,  
1,024 btu/hr, UL/CUL

**Features:** Push button operation, one adjustable shelf, accuracy  $\pm 1^\circ$  F

**Comfort C21**  
**Overall Size (h x w x d)**  
74.5" x 30" x 26.5"  
**Chamber I.D.**  
61" x 26" x 23"  
21 cubic-ft. storage  
**Electrical**  
120 V, 7.5 Amp., 50/60 Hz,  
.53 kw/hr, 1,810 btu/hr,  
UL/CUL

**Features:** Push button operation, two adjustable shelves, two fixed shelves, accuracy  $\pm 3^\circ$  F



**Comfort Compact**  
**Overall Size (h x w x d)**  
24.5" x 24" x 20.5"  
**Chamber I.D.**  
15.25" x 20" x 17"  
3 cubic-ft. storage  
**Electrical**  
120 V, 3.5 Amp.,  
50/60 Hz, .45 kw/hr,  
1,537 btu/hr, UL/CUL

**Features:** Push button operation, optional adjustable shelf, accuracy  $\pm 1^\circ$  F



**Comfort C5**  
**Overall Size (h x w x d)**  
24.5" x 30" x 26.5"  
**Chamber I.D.**  
15.25" x 26" x 23"  
5.27 cubic-ft. storage  
**Electrical**  
120 V, 7.5 Amp.,  
50/60 Hz, .30 kw/hr,  
1,024 btu/hr, UL/CUL

**Features:** Push button operation, one adjustable shelf, accuracy  $\pm 1^\circ$  F

**Comfort C9**  
**Overall Size (h x w x d)**  
36" x 30" x 26.5"  
**Chamber I.D.**  
25" x 26" x 23"  
8.63 cubic-ft. storage  
**Electrical**  
120 V, 7.5 Amp., 50/60 Hz,  
.35 kw/hr, 1,195 btu/hr,  
UL/CUL

**Features:** Push button operation, two adjustable shelves, fully insulated